

TEST REPORT

Applicant : Shenzhen Growatt New Energy Co., Ltd.
Address : 4-13/F, Building A, Sino-German (Europe) Industrial Park, Hangcheng Ave, Bao'an District, Shenzhen, China.

Report No : 230731030GZU-003 **Issue Date** : 15 Sep 2023

Sample Description

Name of Sample : PV Micro Inverter
Model Number : NEO 600M-X, NEO 800M-X, NEO 1000M-X
Quantity of Sample(s) : 1
Date of Receival : 31 July 2023
Date of test Conducted : 15 Aug 2023

Test

Test Requested : IP67
Test Method : Refer to IEC/EN 62109-1:2010 (First Edition) clause 6.3 (Clause 6.3 requires the test shall be done according to IEC 60529)
Test Observation: : See appendix test condition for details
Test Conclusion: : **Pass**
Other information : --
Remark :

- This test report is only for evaluation of the specified standard clauses listed in Test Requested.
- When determine the test result, measurement uncertainty has been considered.

***** End of page *****

Tested by:

Approved by:

Allen Feng
Engineer

Jason Fu
Supervisor

Note: This document is the property of Intertek Testing Service Shenzhen Ltd. Guangzhou Branch, and it is not transferable. Only the applicant may reproduce it. The testing of this report is type tests. The requirements and tolerances permitted by this report are related to testing of a type-test sample submitted by the manufacturer for that purpose. Compliance of the type-test sample does not ensure compliance of the whole production of a manufacturer.

Note: The testing of this report is type tests. The requirements and tolerances permitted by this report are related to testing of a type-test sample submitted by the manufacturer for that purpose. Compliance of the type-test sample does not ensure compliance of the whole production of a manufacturer.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

The test report only allows to be revised only within the report defined retention period unless standard or regulation was withdrawn or invalid.

Rating

Model	NEO 600M-X	NEO 800M-X	NEO 1000M-X
Max.PV voltage	60Vdc		
MPPT voltage	28-60Vdc		
Max.input current	2*18A		
PV Isc	2*23A		
Nominal output voltage	230Vac		
Nominal output Frequency	50/60Hz		
Rated output current	2.61A	3.48A	4.35A
Max. output power	600W	800W	1000W
Max. apparent power	600VA	800VA	1000VA
Power factor range	0.8Leading~0.8Lagging		
Safety level	Class I		
Ingress Protection	IP 67		
Operation Ambient Temperature	-40°C - +65°C		
Software version	GJ1.0		

Difference of the models:


All models have identical mechanical, except the output power derating in software and hardware differences due to input and output functions.

Appendix test condition:

Number	Test items	Test condition	Test result
1	IP6X	The enclosure under test is supported inside the test chamber and the pressure inside the enclosure is maintained below the surrounding atmospheric pressure by a vacuum pump, The suction connection shall be made to a hole specially provided for the test.	No deposit of dust is observable inside the enclosure.
2	IPX7	<p>The test is made by completely immersing the enclosure in water in its service position as specified by the manufacturer so that the following conditions are satisfied:</p> <p>The lowest point of enclosures with a height less than 850 mm is located 1 000 mm below the surface of the water;</p> <p>The highest point of enclosures with a height equal to or greater than 850 mm is located 150 mm below the surface of the water;</p> <p>The duration of the test is 30 min;</p> <p>The water temperature does not differ from that of the equipment by more than 5 K. However, a modified requirement may be specified in the relevant product standard if the tests are to be made when the equipment is energized and/or its parts in motion.</p>	No water inside the enclosure


***** End of page *****

Appendix Photos:



Front view

***** End of page *****



Bottom view

***** End of page *****

Appendix Photos:



Test setup of IP6X



Test setup of IPX6

Appendix Photos:



Checked after test finish

*****End of report*****